SPECIFICATIONS

No. of cylinders / valves		6L / 4
Turbocharger		WG
Injection System		COMMON RAIL 2200 bar
Displacement	liters	12.9
Bore x Stroke	millimeters	135 x 150
Rated power	kW (HP) @ rpm	407 (553) @ 2100
Max Torque	Nm @ rpm	2401 @ -
ATS		HI-eSCR
Certification		Stage IV / Tier 4 Final

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	1359 x 951 x 1212
Dry Weight	Kg	1320

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS

2400 2000 2000 2000 2000 2000 2000 Engine speed (ppm) 1800 2000 Mightharts com

CURSOR 13

POWER & TORQUE



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

Do you want to know more?

LEGEND

Air Handling

TC (Turbocharged)

NA (Naturally Aspirated)

TCA (Turbocharged with aftercooler)

Turbocharger

WG (Wastegate)

VGT (Variable Geometry Turbocharger)

TST (Twin Stage Turbocharge)

Exhaust System

EGR (Exhaust Gas Recirculation)

SCR (Selective Catalytic Reduction)

DPF (Diesel Particulate Filter)

DOC (Diesel Oxidation Catalyst)

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE



