
SPECIFICATIONS

No. of cylinders / valves		6L / 4
Turbocharger		WG
Injection System		COMMON RAIL 1800 bar
Displacement	liters	8.7
Bore x Stroke	millimeters	117 x 135
Rated power	kW (HP) @ rpm	245 (333) @ 2100
Max Torque	Nm @ rpm	1510 @ -
ATS		HI-eSCR
Certification		Stage IV / Tier 4 Final

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	1216 x 883 x 1007
Dry Weight	Kg	870

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS





IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

Do you want to know more?

LEGEND

Air Handling

TC (Turbocharged)

NA (Naturally Aspirated)

TCA (Turbocharged with aftercooler)

Turbocharger

WG (Wastegate)

VGT (Variable Geometry Turbocharger)

TST (Twin Stage Turbocharge)

Exhaust System

EGR (Exhaust Gas Recirculation)

SCR (Selective Catalytic Reduction)

DPF (Diesel Particulate Filter)

DOC (Diesel Oxidation Catalyst)

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE





CONSTRUCTION