

POWER GENERATION

G-Drive

N45

N45

67 kWm @ 1800 rpm

Tier 3

SPECIFICATIONS

Certification	Tier 3	
No. of cylinders	4L	
Injection System	M	
Air Intake	TC	
Displacement	liters	4.5
Exhaust System	I-EGR	
Stand-by Power @ 1500 rpm	kWm	-
Prime Power @ 1500 rpm	kWm	-
Stand-by Power @ 1800 rpm	kWm	67
Prime Power @ 1800 rpm	kWm	61
Code	NEF45SM2X	

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	1180 x 657 x 1016
Dry Weight	Kg	450

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

Do you want to know more?

LEGEND

Arrangement

L (in line)
V (90° "V" configuration)

Air Handling

TCA (Turbocharged with aftercooler)
TC (Turbocharged)
NA (Naturally Aspirated)

Injection System

M (Mechanical)
ECR (Electronic Common Rail)
EUI (Electronic Unit Injector)
MPI (Multi Point Injection)

MORE INFORMATION ABOUT CONFIGURATIONS AND ACCESSORIES AVAILABILITY, THROUGH THE WORLDWIDE FPT INDUSTRIAL DISTRIBUTORS NETWORK

NOT ALL MODELS, STANDARD EQUIPMENT AND ACCESSORIES ARE AVAILABLE IN ALL COUNTRIES. SPECIFICATIONS AND OPTIONS MAY CHANGE WITHOUT NOTICE

