SPECIFICATIONS

Certification			Stage V / Tier 4 Final
No. of cylinders			6L
Injection System			ECR
Air Intake			TAA
Displacement	liters		6.7
Exhaust System			HI-eSCR2
Stand-by Power @ 1500 rpm		kWm	145
Prime Power @ 1500 rpm		kWm	136
Stand-by Power @ 1800 rpm		kWm	167
Prime Power @ 1800 rpm		kWm	151
Code			N67TEVP06.00

POWER GENERATION

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	1785 x 813 x 1252
Dry Weight	Kg	610

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

Do you want to know more?

LEGEND

Arrangement L (in line)

V (90° "V" configuration)

Air Handling

TC (Turbocharged)

NA (Naturally Aspirated)

TCA (Turbocharged with aftercooler)

Injection System

M (Mechanical)

ECR (Electronic Common Rail)

EUI (Electronic Unit Injector)

MPI (Multi Point Injection)

MORE INFORMATION ABOUT CONFIGURATIONS AND ACCESSORIES AVAILABILITY, THROUGH THE WORLDWIDE FPT INDUSTRIAL DISTRIBUTORS NEYWORK

NOT ALL MODELS, STANDARD EQUIPMENT AND ACCESSORIES ARE AVAILABLE IN ALL COUNTRIES. SPECIFICATIONS AND OPTIONS MAY CHANGE WITHOUT NOTICE



