## **SPECIFICATIONS**

Injection System	Certification			Stage V / Tier 4 Final
Air Intake TAA   Displacement liters 6.7   Exhaust System HI-eSCR2   Stand-by Power @ 1500 rpm kWm 195   Prime Power @ 1500 rpm kWm 176   Stand-by Power @ 1800 rpm kWm 222   Prime Power @ 1800 rpm kWm 201	No. of cylinders			6L
Displacement liters 6.7   Exhaust System HI-eSCR2   Stand-by Power @ 1500 rpm kWm 195   Prime Power @ 1500 rpm kWm 176   Stand-by Power @ 1800 rpm kWm 222   Prime Power @ 1800 rpm kWm 201	Injection System			ECR
Exhaust System HI-eSCR2   Stand-by Power @ 1500 rpm kWm 195   Prime Power @ 1500 rpm kWm 176   Stand-by Power @ 1800 rpm kWm 222   Prime Power @ 1800 rpm kWm 201	Air Intake			TAA
Stand-by Power @ 1500 rpm kWm 195   Prime Power @ 1500 rpm kWm 176   Stand-by Power @ 1800 rpm kWm 222   Prime Power @ 1800 rpm kWm 201	Displacement	liters		6.7
Prime Power @ 1500 rpm kWm 176   Stand-by Power @ 1800 rpm kWm 222   Prime Power @ 1800 rpm kWm 201	Exhaust System			HI-eSCR2
Stand-by Power @ 1800 rpm kWm 222   Prime Power @ 1800 rpm kWm 201	Stand-by Power @ 1500 rpm		kWm	195
Prime Power @ 1800 rpm kWm 201	Prime Power @ 1500 rpm		kWm	176
·	Stand-by Power @ 1800 rpm		kWm	222
Code N67TEVP05.00	Prime Power @ 1800 rpm		kWm	201
	Code			N67TEVP05.00

## **WEIGHT AND DIMENSIONS**

Dimensions (L x W x H)	mm	1785 x 813 x 1252
Dry Weight	Kg	610

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

## Do you want to know more?

LEGEND

Arrangement L (in line)

V (90° "V" configuration)

Air Handling

TCA (Turbocharged with aftercooler)

TC (Turbocharged)

NA (Naturally Aspirated)

Injection System

M (Mechanical)

ECR (Electronic Common Rail)

EUI (Electronic Unit Injector)

MPI (Multi Point Injection)

MORE INFORMATION ABOUT CONFIGURATIONS AND ACCESSORIES AVAILABILITY, THROUGH THE WORLDWIDE FPT INDUSTRIAL DISTRIBUTORS NEYWORK

NOT ALL MODELS, STANDARD EQUIPMENT AND ACCESSORIES ARE AVAILABLE IN ALL COUNTRIES. SPECIFICATIONS AND OPTIONS MAY CHANGE WITHOUT NOTICE



