

# DATA SHEET

## Synchronous Alternator




Customer	: HooverTec LLC	Notes:	
Customer reference	:		
Product line	: GTA201AIHV	Product code	: 14417168
Area classification	: Safe		1010310220

<b>General data</b>		Degree of protection	: IP23
Frame (IEC)	: 200	Mounting style	: B15T
Insulation Class	: 180°C (H)	Number of poles	: 4
THD (L-L, no load)	: ≤ 3%	Type of Pole	: Salient
Stator winding pitch	: 2/3	Rated speed - 50 Hz	: 1500 rpm
Altitude	: up to 1000 m.a.s.l	Nominal rotation - 60 Hz	: 1800 rpm
Number of Leads	: 12	Overspeed	: 2250 rpm
Power factor	: 0.8 to 1.0	Approx. weight	: 245 kg
Excitation system	: Brushless with Auxiliary Coil	Overload	: 1.1x In per 1h each 6h
Cooling	: IC01	Momentary Overload	: 1.5x In per 30s

Frequency and number of phases		50 Hz				60 Hz			
		3ph		1ph	3ph		1ph		
Voltages (V)	Y (series star) connection	380	400	-	380	416	440	480	-
	YY (parallel star) connection	190	200	-	190	208	220	240	-
	Δ (series delta) connection	220	230	-	220	240	254	277	-
	ΔΔ (parallel delta) connection	110	115	-	110	120	127	138	-
	Zig-zag or single phase delta	-	-	-	190 - 200	-	-	-	-
Output power (kVA)	Continuous 80/40	42.0	42.0	23.3	47.3	51.5	54.5	56.4	31.0
	Continuous 105/40	48.5	48.5	26.7	54.2	59.0	62.4	64.6	35.5
	<b>Continuous 125/40</b>	<b>53.0</b>	<b>53.0</b>	<b>29.2</b>	<b>59.1</b>	<b>64.3</b>	<b>68.1</b>	<b>70.5</b>	<b>38.8</b>
	Standby 150/40	56.0	56.0	31.9	63.2	68.8	72.8	77.2	42.5
	Standby 163/27	57.5	57.5	33.3	71.0	73.8	75.7	81.0	44.3
Electrical data (FP=0.8 / Continuous 125/40 (H))	Xd(%) Dir. axis synchronous reactance	280.13	245.76	373.51	361.8	330.0	312.41	272.43	416.54
	X'd(%) Dir. axis transient reactance	24.81	21.74	33.08	32.14	29.24	27.68	24.1	36.91
	X''d(%) Dir. axis subtrans. reactance	20.87	18.31	27.83	27.04	24.6	23.29	20.29	31.05
	Xq(%) Quad. axis sync. reactance	107.02	93.89	142.69	138.19	136.6	119.34	104.08	159.13
	X''q(%) Quad. axis subtrans. react.	18.47	16.19	24.62	23.95	36.55	20.61	17.94	27.48
	X2(%) Negative sequence reactance	19.6	17.18	26.13	25.4	30.57	21.87	19.05	29.16
	X0(%) Zero sequence reactance	3.48	3.05	4.64	4.51	4.1	3.88	3.38	5.18
	T'd(ms) Short Circ.Trans.time const.	56.53	56.63	75.37	56.44	72.32	56.53	56.63	75.37
	T''d(ms) Short Circ. Sub. time const.	1.05	1.05	1.4	1.05	1.26	1.05	1.05	1.4
	T'do(ms) Open Circ. time const Trans	649.05	650.01	865.4	645.52	901.86	648.48	650.01	864.64
	T''do(ms) Open Circ. time const Subt	1.24	1.24	1.66	1.24	1.49	1.24	1.24	1.66
	Ta(ms) Armature time const.	7.52	7.53	10.03	7.51	10.51	7.52	7.53	10.03
	uc(V) Full load excitation voltage	48.66	49.01	48.66	42.79	47.88	47.42	50.57	47.42
	ic(A) Full load excitation current	5.06	5.09	5.06	4.45	4.98	4.93	5.26	4.93
ic(A) No load excitation current	0.7	0.9	0.93	0.4	0.64	0.6	0.8	0.8	
Icc(A) Sustained Short-Circ. Current	241.58	229.5	219.0	269.38	255.3	268.07	254.39	242.34	
Kcc Short-circuit ratio	0.38	0.46	0.5	0.27	0.3	0.33	0.42	0.44	
Efficiency (%)	Power factor	0.8	1.0	0.8	1.0	0.8	1.0	0.8	1.0
	25% of load	89.7	92.4	89.1	92	82.5	85	90.4	93
	50% of load	89.1	92.1	89.2	92.2	82	84.8	89.6	92.3
	75% of load	87	90.6	87.5	91	80	83.4	87.4	90.5
	100% of load	84.7	88.9	85.5	89.5	77.9	81.8	84.9	88.5
	125% of load	82.4	87.1	83.4	88	75.8	80.1	82.5	86.5

<b>Other characteristics</b>		<b>Automatic voltage regulator</b>		<b>According to:</b>	
Air flow	: 0.6 m³/s	Accuracy (stability)	: +/- 0.5%	IEC 60034	
Exciter stator winding resistance at 20°C	: 10.55 ohm	Rated current	: 5 A	NBR 5117	
Stator winding resistance at 20°C	: 0.15532 ohm	Analog input	: Yes	NEMA MG1	
Rotor winding resistance	: 0.82 ohm	Digital input	: No	VDE530	
Stator winding layers	: 2	Peak current	: 7 A/10 s	ISO 8528	
Inertia WR²	: 0.4 kgm²	Droop / TC	: Yes	CSA	
NDE Bearing	: 6210-2RS/ZZ	Dynamic recovery	: 8 to 500 ms		
DE bearing		U/F	: Yes		
Flange	: SAE 4	Internal voltage adjustment	: +/- 15%		
Coupling disc	: SAE 10	External voltage adjustment	: +/- 10%		
		Transient recovery time for ΔU=20%	: 500 ms		

Rev.	Changes Summary	Performed	Checked	Date
Performed by				
Checked by			Page	Revision
Date	08/09/2023		1 /	





TIPO TYPE	DISCOS DISCS	DIMENSÕES: mm / DIMENSIONS: mm								1		2		3		5		Total Weight kg	Total Mom <sub>l</sub> Iner. kgm <sup>2</sup>
		A	B	C	D	E	F	G	WEIGHT MASSA kg	MOMENT MOMENTO kgm <sup>2</sup>	WEIGHT MASSA kg	MOMENT MOMENTO kgm <sup>2</sup>	WEIGHT MASSA kg	MOMENT MOMENTO kgm <sup>2</sup>	WEIGHT MASSA kg	MOMENT MOMENTO kgm <sup>2</sup>			
GTA 201 __HS	SAE 11.5	170.0	327.5	---	580.0	677.0	367.5	699.5	6.4	0.06	0.9	0.01	32.5	0.24	8.0	0.04	47.8	0.35	
GTA 201 __HV			337.5										38.0	53.3			0.39		
GTA 201 __HB			352.5										45.0	60.3			0.44		
GTA 201 __HE			362.5										50.0	65.3			0.47		
GTA 202 __VS			387.5										61.0	76.3			0.55		
GTA 202 __VJ			407.5										70.0	85.3			0.61		

TIPO TYPE	DISCOS DISCS	DIMENSÕES: mm / DIMENSIONS: mm								1		2		3		5		Total Weight kg	Total Mom <sub>l</sub> Iner. kgm <sup>2</sup>
		A	B	C	D	E	F	G	WEIGHT MASSA kg	MOMENT MOMENTO kgm <sup>2</sup>	WEIGHT MASSA kg	MOMENT MOMENTO kgm <sup>2</sup>	WEIGHT MASSA kg	MOMENT MOMENTO kgm <sup>2</sup>	WEIGHT MASSA kg	MOMENT MOMENTO kgm <sup>2</sup>			
GTA 201 __HS	SAE 10	160.5	318.0	---	570.5	667.5	367.5	699.5	5.7	0.04	0.9	0.01	32.5	0.24	8.0	0.04	47.8	0.35	
GTA 201 __HV			328.0										38.0	53.3			0.39		
GTA 201 __HB			343.0										45.0	60.3			0.44		
GTA 201 __HE			353.0										50.0	65.3			0.47		
GTA 202 __VS			378.0										61.0	75.6			0.53		
GTA 202 __VJ			398.0										70.0	85.3			0.61		

PESO BRUTO / GROSS WEIGHT		kg	PESO LÍQUIDO / NET WEIGHT		kg	ESC / SCALE	1:4			
EMISSÃO INICIAL / INITIAL EMISSION										
ECM ECM	LOC LOC	RESUMO MODIFICAÇÃO SUMMARY OF MODIFICATIONS				EXECUTADO EXECUTED	VERIFICADO CHECKED	LIBERADO RELEASED	DATA DATE	VER VER
EXEC. / EXECUTED		ANÁLISE TORSIONAL LINHA G-PLUS 200 B15				10009091390				
VERIF. / CHECKED						000		00		
LIBER. / RELEASED										
DATA LB / REL DT		JARAGUA DO SUL	ENGENHARIA DO PRODUTO	FOLHA / SHEET	01 / 01					





PESO BRUTO / GROSS WEIGHT		PESO LIQUIDO / NET WEIGHT		ESC / SCALE	1:8			
ECM ECM	LOC LOC	RESUMO MODIFICAÇÃO SUMMARY OF MODIFICATIONS		EXECUTADO EXECUTED	VERIFICADO CHECKED	LIBERADO RELEASED	DATA DATE	VER VER
EXEC. / EXECUTED		DIMENSIONAL GTA201 B15T						
VERIF. / CHECKED								
LIBER. / RELEASED								
DATA LB / REL DT	29.01.2018	WEN	JARAGUA DO SUL	ALTERNADORES GENSET	FOLHA / SHEET	01 / 01	10005056123	000   03

