# G-DRIV

## **SPECIFICATIONS**

Certification			Tier 3
No. of cylinders			6L
Injection System			EUI
Air Intake			TAA
Displacement	liters		12.9
Exhaust System			I-EGR
Stand-by Power @ 1500 rpm		kWm	-
Prime Power @ 1500 rpm		kWm	-
Stand-by Power @ 1800 rpm		kWm	371
Prime Power @ 1800 rpm		kWm	337
Code			CURSOR13TE3

## **WEIGHT AND DIMENSIONS**

Dimensions (L x W x H)	mm	2324 x 1270 x 1546
Dry Weight	Kg	1228

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

# Do you want to know more?

### LEGEND

Arrangement L (in line)

V (90° "V" configuration)

Air Handling

TCA (Turbocharged with aftercooler)

TC (Turbocharged)

NA (Naturally Aspirated)

Injection System

M (Mechanical)

ECR (Electronic Common Rail)

EUI (Electronic Unit Injector)

MPI (Multi Point Injection)

MORE INFORMATION ABOUT CONFIGURATIONS AND ACCESSORIES AVAILABILITY, THROUGH THE WORLDWIDE FPT INDUSTRIAL DISTRIBUTORS NEYWORK

NOT ALL MODELS, STANDARD EQUIPMENT AND ACCESSORIES ARE AVAILABLE IN ALL COUNTRIES. SPECIFICATIONS AND OPTIONS MAY CHANGE WITHOUT NOTICE



