3-DRIVE

POWER GENERATION G-Drive CURSOR 13

CURSOR 13
387 kWm @ 1800 rpm
Stage V - Tier 4 Final


SPECIFICATIONS

Certification			Stage V - Tier 4 Final
No. of cylinders			6L
Injection System			ECR
Air Intake			TAA
Displacement	liters		8.7
Exhaust System			HI-eSCR2
Stand-by Power @ 1500 rpm		kWm	346
Prime Power @ 1500 rpm		kWm	313
Stand-by Power @ 1800 rpm		kWm	387
Prime Power @ 1800 rpm		kWm	350
Code			C13TEVP03.A36

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	2281 x 1223 x 1454
Dry Weight	Kg	1399

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

Do you want to know more?

LEGEND

Arrangement

L (in line)

V (90° "V" configuration)

Air Handling

TCA (Turbocharged with aftercooler)
TC (Turbocharged)

NA (Naturally Aspirated)

Injection System

M (Mechanical)

ECR (Electronic Common Rail)

EUI (Electronic Unit Injector)

MPI (Multi Point Injection)

MORE INFORMATION ABOUT CONFIGURATIONS AND ACCESSORIES AVAILABILITY, THROUGH THE WORLDWIDE FPT INDUSTRIAL DISTRIBUTORS NEYWORK

NOT ALL MODELS, STANDARD EQUIPMENT AND ACCESSORIES ARE AVAILABLE IN ALL COUNTRIES. SPECIFICATIONS AND OPTIONS MAY CHANGE WITHOUT NOTICE



